

LIGEO W				ABMESSUNGEN			LICHTWERTE					
Artikel Nr.:	Artikel Nr.:	Artikel Nr.:	Artikel Nr.:	Lichtfeld	Stichmaß	Gesamtmaß	Gewicht	Lichtstrom	Leistung	Kelvin	Ra	Energieeffizienzklasse
Silber eloxiert	Schwarz eloxiert	Gold eloxiert	Weiss*	(mm)	(mm)	(mm)	(g)	(lm)	(W)			
Leuchten												
W3	29003010130	29003020130	29003030130	29003040130	300	395	428	117	492	5.7	3000	83.1 A+
	29003010140	29003020140	29003030140	29003040140	300	395	428	117	474	5.6	4000	86.4 A+
	29003010150	29003020150	29003030150	29003040150	300	395	428	117	507	5.6	5300	86.5 A+
W6	29006010130	29006020130	29006030130	29006040130	600	695	728	198	984	11.4	3000	83.1 A+
	29006010140	29006020140	29006030140	29006040140	600	695	728	198	949	11.3	4000	86.4 A+
	29006010150	29006020150	29006030150	29006040150	600	695	728	198	1015	11.3	5300	86.5 A+
W9	29009010130	29009020130	29009030130	29009040130	900	995	1028	287	1476	17.1	3000	83.1 A+
	29009010140	29009020140	29009030140	29009040140	900	995	1028	287	1423	17.1	4000	86.4 A
	29009010150	29009020150	29009030150	29009040150	900	995	1028	287	1522	17.1	5300	86.5 A+
W12	29012010130	29012020130	29012030130	29012040130	1200	1295	1328	370	1968	22.8	3000	83.1 A+
	29012010140	29012020140	29012030140	29012040140	1200	1295	1328	370	1897	22.6	4000	86.4 A
	29012010150	29012020150	29012030150	29012040150	1200	1295	1328	370	2030	22.6	5300	86.5 A+
W15	29015010130	29015020130	29015030130	29015040130	1500	1595	1628	452	2460	28.5	3000	83.1 A+
	29015010140	29015020140	29015030140	29015040140	1500	1595	1628	452	2372	28.2	4000	86.4 A
	29015010150	29015020150	29015030150	29015040150	1500	1595	1628	452	2537	28.2	5300	86.5 A+
Knoten												
VK	29000900100	29000900200	29000900300	29000900400	(Verbinder-Knoten)			28				
EK	29000900110	29000900210	29000900310	29000900410	(Einspeiser-Knoten)			30				

*Weisse Knoten, silberne Aluminiumprofile